

Final Product/Process Change Notification Document #: FPCN24928Z Issue Date: 23 Jan 2023

Title of Change:	Schottky Metallization Change And Lead Frame Modification for SOD 123 FL Package.		
Proposed Changed Material First Ship Date:	01 Feb 2024 or earlier if approved by customer		
Current Material Last Order Date:	N/A Orders received after the Current Material Last Order Date expiration are to be considered as orders for new changed material as described in this PCN. Orders for current (unchanged) material after this date will be per mutual agreement and current material inventory availability.		
Current Material Last Delivery Date:	N/A The Current Material Last Delivery Date may be subject to change based on build and depletion of the current (unchanged) material inventory		
Product Category:	Active components – Discrete components		
Contact information:	Contact your local onsemi Sales Office or SitiNurhaza.MohdRamli@onsemi.com		
PCN Samples Contact:	Contact your local onsemi Sales Office to place sample order. Sample requests are to be submitted no later than 45 days after publication of this change notification. Samples delivery timing will be subject to request date, sample quantity and special customer packing/label requirements.		
Sample Availability Date:	13 Feb 2023		
PPAP Availability Date:	13 Feb 2023		
Additional Reliability Data:	Contact your local onsemi Sales Office or MohdAzizi.Azman@onsemi.com		
Type of Notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. The change will be implemented at 'Proposed Change Material First Ship Date' in compliance to J-STD-46 or ZVEI, or earlier upon customer approval, or per our signed agreements. onsemi will consider this proposed change and it's conditions acceptable, unless an inquiry is made in writing within 45 days of delivery of this notice. To do so, contact PCN.Support@onsemi.com.		
Change Category			
Category	Type of Change		
Bare Die	New / change of frontside metallization, New / change of backside metallization		
Process - Assembly	Change in leadframe dimensions		

TEM001794 Rev. G Page 1 of 3



Final Product/Process Change Notification

Document #: FPCN24928Z Issue Date: 23 Jan 2023

Description and Purpose:

This is the final product change notification (FPCN) of IPCN24928Z, announcing that onsemi is qualifying Schottky

Metallization Change and Leadframe modification on selected automotive qualified Orderable Part Numbers (OPNs) listed in this FPCN.

This changes already implement to commercial SOD 123 FL part number. Detail changes as below.

	From	То	
Top metalization	TiW/NiV/Au	TiW/NiV/Ag	
Back Metalization	Cr/Ni/Au	Ti/Ni/Ag	
Leadframe	Interlock Groove CURRENT	Flat Groove PROPOSED	

Products had gone thru reliability testing as per automotive requirements and it's proven that device performances are not affected.

There is no product marking change as a result of this change.

Reason / Motivation for Change:	Quality improvement		
Anticipated impact on fit, form, function, reliability, product safety or manufacturability:	The device has been qualified and validated based on the same Product Specification. The device has successfully passed the qualification tests. Potential impacts can be identified, but due to testing performed by onsemi in relation to the PCN, associated risks are verified and excluded. No anticipated impacts.		
Sites Affected: onsemi Sites	The distributed impacts.	External Foundry/Subcon Sites	
onsemi Seremban, Malaysia onsemi, ISMF Malaysia		None	
Marking of Parts/ Traceability of Change:	By date code		

TEM001794 Rev. G Page 2 of 3



Final Product/Process Change Notification

Document #: FPCN24928Z Issue Date: 23 Jan 2023

Reliability Data Summary:

QV DEVICE NAME: NRVB2H100SFT3G

RMS: S72133

PACKAGE: SOD-123FL

Test	Specification	Condition		Results
HTRB	JESD22-A108	Ta=90°C, 100% max rated V		0/231
PC	J-STD-020 JESD-A113	MSL 1 @ 260 °C, Pre IOL, TC, uHAST, H3TRB for surface mount pkgs only		0/924
IOL	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min		0/231
TC	JESD22-A104	Ta= -55°C to +150°C, mount on board		0/231
H3TRB	JESD22-A110	85°C, 85% RH, bias		0/231
uHAST	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased		0/231
RSH	JESD22- B106	Ta = 265°C, 10 sec Required for through hole devices only		0/90
SD	JSTD002	Ta = 245°C, 5 sec		0/45

NOTE: AEC-1pager is attached.

To view attachments:

- ${\it 1. Download pdf copy of the PCN to your computer}\\$
- 2. Open the downloaded pdf copy of the PCN
- 3. Click on the paper clip icon available on the menu provided in the left/bottom portion of the screen to reveal the Attachment field
- 4. Then click on the attached file.

Electrical Characteristics Summary:

Electrical characteristics are not impacted.

List of Affected Parts:

Note: Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the **PCN Customized Portal**.

Current Part Number	New Part Number Qualification Vehicle	
NRVB2H100SFT3G	NA	NRVB2H100SFT3G
NRVB230LSFT1G	NA	NRVB2H100SFT3G
NRVB1H100SFT3G	NA	NRVB2H100SFT3G
NRVB140ESFT3G	NA	NRVB2H100SFT3G
NRVB140ESFT1G	NA	NRVB2H100SFT3G
NRVB130LSFT1G	NA	NRVB2H100SFT3G
NRVB120VLSFT1G	NA	NRVB2H100SFT3G

TEM001794 Rev. G Page 3 of 3



Appendix A: Changed Products

PCN#: FPCN24928Z Issue Date: Jan 23, 2023

DIKG: DIGI-KEY

Product	Customer Part Number	Qualification Vehicle	New Part Number	Replacement Supplier
NRVB2H100SFT3G		NRVB2H100SFT3G	NA	
NRVB1H100SFT3G		NRVB2H100SFT3G	NA	
NRVB140ESFT3G		NRVB2H100SFT3G	NA	
NRVB140ESFT1G		NRVB2H100SFT3G	NA	
NRVB230LSFT1G		NRVB2H100SFT3G	NA	
NRVB120VLSFT1G		NRVB2H100SFT3G	NA	
NRVB130LSFT1G		NRVB2H100SFT3G	NA	