IPC ASSOCIATION OF ELECTRONICS	© Copyright 200:	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.		This docum level parts,	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No. Homogeneous Materi				als and Mfg	Informatio	on	
upplier 1	Information					,			,				
Company name*			Company unique ID			Unique ID Authority				Response Date*			
nsemi						I				2023-06-08			
Contact Nai	me		Title - Contact			Phone - Contact*				Email - Contact*			
Product-En	nv-Stewards		Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
uthorized	Representative*		Title - Representative			Phone - Representative*			Email - Representative*				
Product-En	nv-Stewards		Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
	Requester Item Number	Mfr Item	Number	Mfr Item Name		Effective D	ate Vers	Version Manufacturing Site		W	eight*	UOM	Unit Type
				150V, 100mA VH' wettable flanks	V LDO ADJ 3.3V HZ non	2023-06-08			MY1		2.24	mg	Each
Ianufact	turing Proccess Inform	nation											
Т	<u> </u>		Terminal Base Alloy J-STD-020		STD-020 MSL Rating	Peak Process Body Tempera		ure Max Time at Peak	Temperatu	re Numbe	r of Reflow Cyc	les	
N	Matte Tin (Sn) - annealed	(CU Alloy	1		260		C	30	second	3		
omments													
<u>vel 1 - max</u>	ximum time at peak temper	ature during sol	dering is 10-3	0 seconds									
or more in	formation regarding mater	ial composition	please refer to	page 3									

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier have provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.92	mg	Supplier	Silicon (Si)	7440-21-3		0.92	mg
Die Attach	0.16		Supplier	Silver (Ag)	7440-22-4		0.1224	mg
			Supplier	Epoxy resins	129915-35-1		0.0376	mg
Lead Frame	5.86		Supplier	Silver (Ag)	7440-22-4		0.1172	mg
			Supplier	Zinc (Zn)	7440-66-6		0.007	mg
			Supplier	Iron (Fe)	7439-89-6		0.1377	mg
			Supplier	Copper (Cu)	7440-50-8		5.5963	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0018	mg
Mold Compound-Black	14.8	mg		Epoxy resin	proprietary data		1.11	mg
			Supplier	Phenolic Resin	Proprietary Data		0.37	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		1.11	mg
			Supplier	Carbon Black (C)	1333-86-4		0.074	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		12.136	mg
Plating	0.38	mg	Supplier	Tin (Sn)	7440-31-5		0.38	mg
Wire Bond - Au	0.12	mg	Supplier	Gold (Au)	7440-57-5		0.12	mg