IPC ASSOCIATION ELECTRONIC	© Copyright 200	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			T le	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
1752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				erials and N	ials and Mfg Information				
Supplie	r Information														
Company	name*	Company un	Company unique ID			Unique ID Authority				Respor	Response Date*				
nsemi											2023-0	2023-06-08			
Contact N	ame		Title - Conta	Title - Contact			Phone - Contact*				Email -	Email - Contact*			
Product-l	Env-Stewards		Product Enviro Compliance]	NA				Produ	Product-Env-Stewards@onsemi.com			
uthorize	d Representative*		Title - Representative			I	Phone - Representative*				Email -	Email - Representative*			
Product-l	Env-Stewards		Product Enviro Compliance			1	NA				Produ	Product-Env-Stewards@onsemi.com			
	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date Version Manufacturing		anufacturing Site		Weight*	UOM	Unit Type		
		FAN6604MRMX Green Mode PWM		I Cntlr		2023-06-08	TAD			80.99889	mg	Each			
I anufa	cturing Proccess Infor													·	
	3		,		-STD-020 MSL 1	Rating			dy Temperature Max Time at Peak		<u> </u>		er of Reflow Cyc	eles	
Matte Tin (Sn) - annealed CU Alloy			CU Alloy	1			260		C	30	seco	nds 3			
omments															
<u>vel 1 - m</u>	aximum time at peak temper	ature during so	ldering is 10-3	30 seconds											
or more	information regarding mater	ial composition	please refer to	o page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.38	mg	Supplier	Silicon (Si)	7440-21-3		2.38	mg
Die Attach	0.064696	mg	Supplier	Silver (Ag)	7440-22-4		0.0505	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.0142	mg
Lead Frame	25.9192	mg	Supplier	Silver (Ag)	7440-22-4		0.2074	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0259	mg
			Supplier	Iron (Fe)	7439-89-6		0.5443	mg
			Supplier	Copper (Cu)	7440-50-8		25.1157	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0259	mg
Mold Compound-Black	50.124	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		6.0149	mg
			Supplier	Carbon Black (C)	1333-86-4		0.5012	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		42.6054	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		1.0025	mg
Plating	2.43	mg	Supplier	Tin (Sn)	7440-31-5		2.43	mg
Wire Bond - Au	0.081	mg	Supplier	Gold (Au)	7440-57-5		0.081	mg