ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES® Material Composition © Copyright 2005. IPC, Bann international and Pan-America	ockburn, Illinois. A	ll rights reserved un ntions.	ider both	This docume evel parts, t	ent is a declara he declaration	tion of the encompass	substance ses all low	s within the manufactor er level materials for	urer listed which the 1	item. Note: nanufacture	if the item is an as er has engineering	sembly with lower responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Ty http://www.ipc.org/IPC-175x Distribut			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Info					Ifg Informa	tion			
Supplier Information													
Company name* Company unique ID				Unique ID Authority				Response Date*					
onsemi	nsemi								2023-00	2023-06-08			
Contact Name	Title - Contact			1	Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards	v-Stewards Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
uthorized Representative* Title - Representative				Phone - Representative*				Email -	Email - Representative*				
Product-Env-Stewards Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com				
Requester Item Number Mfr	Mfr Item Number		Mfr Item Name		Effective Dat	e Versio	n	Manufacturing Site		Weight*	UOM	Unit Type	
NCF	NCP170AXV180T2G Ultra-Low IQ 150 Regulator, Act Dis				2023-06-08	3 CN1			2.79	mg	Each		
Manufacturing Proccess Information													
Terminal Plating / Grid Array Material	Terminal Plating / Grid Array Material Terminal Base Alloy J-			Rating	Peak Pro	cess Body '	Temperati	are Max Time at Pea	k Tempera	ture Num	ber of Reflow Cyc	eles	
Matte Tin (Sn) - annealed CU Alloy 1					260		С	30	secon	nds 3			
Comments													
level 1 - maximum time at peak temperature durin	g soldering is 10-3	0 seconds											
For more information regarding material composit	ion please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted	
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.12	mg	Supplier	Silicon (Si)	7440-21-3		0.12	mg
Lead Frame 1.18	1.18	mg	В	Nickel (Ni)	7440-02-0		0.4283	mg
			Supplier	Iron (Fe)	7439-89-6		0.5924	mg
			Supplier	Copper (Cu)	7440-50-8		0.1593	mg
Mold Compound-Black 1.4	1.4	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.042	mg
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.007	mg
			Supplier	2,4,6-triamino-1,3,5-triazine isocyanuric acid	37640-57-6		0.042	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		1.12	mg
			Supplier	Carbon Black (C)	1333-86-4		0.014	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.112	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.063	mg
Plating	0.06	mg	Supplier	Tin (Sn)	7440-31-5		0.06	mg
Wire Bond - Au	0.03	mg	Supplier	Gold (Au)	7440-57-5		0.03	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).