



Image may be representation.
See specifications for product details.



LM385D-1.2R2G

Manufacturer Part Number	LM385D-1.2R2G
Manufacturer	onsemi
Allelco Part Number	32D-LM385D-1.2R2G
ECAD Model	PCB Symbol, Footprint & 3D Model
Parts Description	IC VREF SHUNT -2.4%/+2.01% 8SOIC
Package	8-SOIC (0.154", 3.90mm Width)
Data sheet	Cylindrical Battery Holders.pdf
	LM285, LM385B.pdf
RoHs Status	ROHS3 Compliant

Get a Quote

LM385D-1.2R2G - onsemi.New Original in Stock. Download Linear Technology LM385D-1.2R2G datasheet/specifications on AllelcoElec.com.
Request a quote for LM385D-1.2R2G, please send us email: info@allelco.com

Specifications

LM385D-1.2R2G Tech Specifications

LM385D-1.2R2G - onsemi technical specifications, attributes, parameters

Product Attribute	Attribute Value	Product Attribute	Attribute Value
Manufacturer	onsemi	Output Type	Fixed
Voltage - Output (Min/Fixed)	1.235V	Operating Temperature	0°C ~ 70°C (TA)
Voltage - Input	-	Noise - 10Hz to 10kHz	60µVrms
Tolerance	-2.4%, +2.01%	Noise - 0.1Hz to 10Hz	-
Temperature Coefficient	80ppm/°C Typical	Mounting Type	Surface Mount
Supplier Device Package	8-SOIC	Current - Supply	-
Series	-	Current - Output	20 mA
Reference Type	Shunt	Current - Cathode	20 µA
Package / Case	8-SOIC (0.154", 3.90mm Width)	Base Product Number	LM385
Package	Tape & Reel (TR)		

Parts with Similar Specifications

The three parts on the right have similar specifications to onsemi LM385D-1.2R2G

Product Attribute				
Part Number	LM385D-1.2R2G	LM385D-1-2	LM385D-2-5	LM385DR-2-5
Manufacturer	onsemi	Texas Instruments	Texas Instruments	Texas Instruments
Current - Cathode	20 µA	15 µA	20 µA	20 µA
Current - Output	20 mA	20 mA	20 mA	20 mA
Noise - 10Hz to 10kHz	60µVrms	60µVrms	120µVrms	120µVrms
Operating Temperature	0°C ~ 70°C (TA)	0°C ~ 70°C (TA)	0°C ~ 70°C (TA)	0°C ~ 70°C (TA)
Tolerance	-2.4%, +2.01%	±2%	±3%	±3%
Voltage - Input	-	-	-	-
Noise - 0.1Hz to 10Hz	-	-	-	-
Mounting Type	Surface Mount	Surface Mount	Surface Mount	Surface Mount
Temperature Coefficient	80ppm/°C Typical	20ppm/°C Typical	20ppm/°C Typical	20ppm/°C Typical
Reference Type	Shunt	Shunt	Shunt	Shunt
Current - Supply	-	-	-	-
Package / Case	8-SOIC (0.154", 3.90mm Width)	8-SOIC (0.154", 3.90mm Width)	8-SOIC (0.154", 3.90mm Width)	8-SOIC (0.154", 3.90mm Width)
Series	-	-	-	-
Supplier Device Package	8-SOIC	8-SOIC	8-SOIC	8-SOIC
Base Product Number	LM385	LM385	LM385	LM385
Voltage - Output (Min/Fixed)	1.235V	1.235V	2.5V	2.5V
Package	Tape & Reel (TR)	Tube	Tube	Tape & Reel (TR)
Output Type	Fixed	Fixed	Fixed	Fixed

LM385D-1.2R2G Datasheet PDF

Download LM385D-1.2R2G pdf datasheets and onsemi documentation for LM385D-1.2R2G - onsemi.

Datasheets

[Cylindrical Battery Holders.pdf](#)


Environmental Information

[onsemi RoHS.pdf](#)

[Material Declaration LM385D-1.2R2G.pdf](#)



















PCN Packaging

[2.73KHz.pdf](#)

 LM285, LM385B.pdf

Customers Also Interested in

Recommended Products

					
LM385D-1-2 Texas Instruments IC VREF SHUNT 2% 8SOIC	LM385D-2-5 Texas Instruments IC VREF SHUNT 3% 8SOIC	LM385DG4-2-5 Texas Instruments	LM385DR-2-5 Texas Instruments IC VREF SHUNT 3% 8SOIC	LM385DR-1-2 Texas Instruments IC VREF SHUNT 2% 8SOIC	LM385D-2.5R2 onsemi IC VREF SHUNT 3% 8SOIC
					
LM385DG4-1-2 Texas Instruments IC VREF SHUNT 2% 8SOIC	LM385BZ-1.2G onsemi IC VREF SHUNT 1% TO92-3	LM385D-1.2G onsemi ANA MICROPWR V-REG DIODE	LM385D-1.2R2 onsemi IC VREF SHUNT -2.4%/+2.01% 8SOIC	LM385D-2.5G onsemi IC VREF SHUNT 3% 8SOIC	LM385D-2.5R2G onsemi IC VREF SHUNT 3% 8SOIC
					
LM385D-1.2 onsemi IC VREF SHUNT -2.4%/+2.01% 8SOIC	LM385BZ-2.5 onsemi IC VREF SHUNT 1.5% TO92-3	LM385BZ-2.5G onsemi IC VREF SHUNT 1.5% TO92-3	LM385CS 0	LM385D-2.5 onsemi IC VREF SHUNT 3% 8SOIC	LM385BZ-2.5 Texas Instruments IC VREF SHUNT 1.5% TO92-3

Shipment

Delivery Time

In-stock items can be shipped within 24 hours. Some parts will be arranged for delivery within 1-2 days from the date all items arrive at our warehouse. And Allelco ships order once a day at about 17:00, except Sunday. Once the goods are shipped, the estimated delivery time depends on the shipping methods and Delivery destination. The table below shows are the logistic time for some common countries.

Delivery Cost

- > Use your express account for shipment if you have one.
 - > Use our account for the shipment. Refer to the table below for the approximate charges.
- (Different time frame / countries / package size has different price.)

Delivery Method

- > Global Common Shipment by DHL / UPS / FedEx / TNT / EMS / SF we support.
- > Others more shipping ways, please get in touch with your customer manager.

Common Countries Logistic Time Reference		
Region	Country	Logistic Time(Day)
America	United States	5
	Brazil	7
Europe	Germany	5
	United Kingdom	4
	Italy	5
Oceania	Australia	6
	New Zealand	7
Asia	India	6
	Japan	7
Middle East	Israel	6

DHL & FedEx Shipment Charges Reference	
Shipment charges(KG)	Reference DHL(USD\$)
0.00kg-1.00kg	USD\$60.00
1.00kg-2.00kg	USD\$70.00
2.00kg-3.00kg	USD\$80.00




Note: The above table is for reference only. There may have some data bias for the uncontrollable factors. Contact us if you have any questions.

Payment Support



The payment method can be chosen from the methods shown below:
Wire Transfer (T/T, Bank Transfer), Western Union, Credit card, PayPal.



Your Faithful Supply Chain Partner -

 Efficient Supply Management	 Cost-Saving Procurement	 Fast Sourcing & Delivery
--	--	---

Contact us if you have any questions.

 Phone +00852 9146 4856	 Email info@allelco.com
--	--

Certifications & Memberships



[View More](#)

Contact us

Address: Flat/Rm C 13/F Harvard Commercial Building 105-111 Thomson Road, Wan Chai, Hong Kong
Phone: +00852 9146 4856
Fax: +00852 3010 8510
Email: info@Allelco.com