Get a Quote



L78M24CDT-TR

Manufacturer

RoHs Status

Manufacturer Part Number L78M24CDT-TR

Allelco Part Number 32D-L78M24CDT-TR

PCB Symbol, Footprint & 3D Mode ECAD Model

IC REG LINEAR 24V 500MA DPAK Parts Description

TO-252-3, DPak (2 Leads + Tab), SC-63 Package

STMicroelectronics

L78M24CDT-TR.pdf Data sheet ROHS3 Compliant

L78M24CDT-TR - STMicroelectronics.New Original in Stock. Download Linear Technology L78M24CDT-TR datasheet/specifications on AllelcoElec.com. Request a quote for L78M24CDT-TR, please send us email: info@allelco.com

Image may be representation.

See specifications for product details.

Specifications

L78M24CDT-TR Tech Specifications

 ${\it L78M24CDT-TR-STMicroelectronics\ technical\ specifications,\ attributes,\ parameters}$

Exorizines from the object of				
Product Attribute	Attribute Value	Product Attribute	Attribute Value	
Manufacturer	STMicroelectronics	PSRR	50dB (120Hz)	
Voltage Dropout (Max)	-	Output Type	Fixed	
Voltage - Output (Min/Fixed)	24V	Output Configuration	Positive	
Voltage - Output (Max)	-	Operating Temperature	0°C ~ 125°C	
Voltage - Input (Max)	40V	Number of Regulators	1	
Supplier Device Package	DPAK	Mounting Type	Surface Mount	
Series	-	Current - Quiescent (Iq)	6 mA	
Protection Features	Over Current, Over Temperature, Short Circuit	Current - Output	500mA	
Package / Case	TO-252-3, DPak (2 Leads + Tab), SC-63	Control Features	-	
Package	Tape & Reel (TR)	Base Product Number	L78M24	

Parts with Similar Specifications

The three parts on the right have similar specifications to STMicroelectronics L78M24CDT-TR

The three parts on the right have similar specifications to STMicroelectronics L/8M24CD1-TR				
Product Attribute				
Part Number	L78M24CDT-TR	L78M24ABDT-TR	L78M24CV-DG	L78M15CV-DG
Manufacturer	STMicroelectronics	STMicroelectronics	STMicroelectronics	STMicroelectronics
Voltage - Input (Max)	40V	40V	40V	35V
Current - Quiescent (Iq)	6 mA	6 mA	6 mA	6 mA
Mounting Type	Surface Mount	Surface Mount	Through Hole	Through Hole
Base Product Number	L78M24	L78M24	L78M24	L78M15
PSRR	50dB (120Hz)	50dB (120Hz)	50dB (120Hz)	54dB (120Hz)
Voltage Dropout (Max)	-	-	-	-
Voltage - Output (Min/Fixed)	24V	24V	24V	15V
Number of Regulators	1	1	1	1
Output Configuration	Positive	Positive	Positive	Positive
Control Features	-	-	-	-
Output Type	Fixed	Fixed	Fixed	Fixed
Current - Output	500mA	500mA	500mA	500mA
Package / Case	TO-252-3, DPak (2 Leads + Tab), SC-63	TO-252-3, DPak (2 Leads + Tab), SC-63	TO-220-3	TO-220-3
Package	Tape & Reel (TR)	Tape & Reel (TR)	Tube	Tube
Voltage - Output (Max)	-	-	-	-
Operating Temperature	0°C ~ 125°C	-40°C ∼ 125°C	0°C ∼ 125°C	0°C ~ 150°C
Protection Features	Over Current, Over Temperature, Short Circuit			
Series	-	-	-	-
Supplier Device Package	DPAK	DPAK	TO-220	TO-220

■ L78M24CDT-TR Datasheet PDF

Download L78M24CDT-TR pdf datasheets and STMicroelectronics documentation for L78M24CDT-TR - STMicroelectronics.

PCN Packaging



Mult Dev Inner Box Chg 9/Dec/2021.pdf

Customers Also Interested in









L780S05





L78M18CV

STMicroelectronics

L78MR05L-FA

AMI Semiconductor/onsemi



IC REG LINEAR 24V 500MA DPAK

STMicroelectronics AMI Semiconductor/onsemi

L78M24CV-DG

STMicroelectronics IC REG LINEAR 24V 500MA L78M24CDT MOS

STMicroelectronics













L78M18CDT-TR

STMicroelectronics



STMicroelectronics





IC REG LINEAR 15V 500MA TO220

L78M24CDT-TR MOS

L78M24CV

STMicroelectronics IC REG LINEAR 24V 500MA TO220AB



L78M24CDT

STMicroelectronics

IC REG LINEAR 24V 500MA DPAK

life.augmented

L78M18CDT STMicroelectronics













L78M15CX

L78MR05-FA

L78N05

L78M24ABDTTR



L78MR05



STMicroelectronics

AMI Semiconductor/onsemi

AMI Semiconductor/onsemi

AMI Semiconductor/onsemi

STMicroelectronics



L78M15CV

STMicroelectronics

IC REG LINEAR 15V 500MA TO220AB

Shipment

Delivery Time

In-stock items can be shipped within 24 hours. Some parts will be arranged for delivery within 1-2 days from the date all items arrive at our warehouse. And Allelco ships order once a day at about 17:00, except Sunday. Once the goods are shipped, the estimated delivery time depends on the shipping methods and Delivery destination. The table below shows are the logistic time for some common countries.

Delivery Cost

- > Use your express account for shipment if you have one.
- > Use our account for the shipment. Refer to the table below for the approximate charges.

(Different time frame / countries / package size has different price.)

Delivery Method

- > Global Common Shipment by DHL / UPS / FedEx / TNT / EMS / SF we support.
- > Others more shipping ways, please get in touch with your customer manager.

Country Ited States	Logistic Time(Day) 5
ted States	5
zil	7
rmany	5
ted Kingdom	4
У	5
stralia	6
w Zealand	7
lia	6
an	7
ael	6
it it	many ted Kingdom y tralia v Zealand ia

DHL & FedEx Shipment Charges Reference			
Shipment charges(KG)	Reference DHL(USD\$)		
0.00kg-1.00kg	USD\$60.00		
1.00kg-2.00kg	USD\$70.00		
2.00kg-3.00kg	USD\$80.00		

Note: The above table is for reference only. There may have some data bias for the uncontrollable factors. Contact us if you have any questions.

Payment Support

The payment method can be chosen from the methods shown below: Wire Transfer (T/T, Bank Transfer), Western Union, Credit card, PayPal.











Your Faithful Supply Chain Partner -




Management









Procurement



+00852 9146 4856

















View More



Copyright © 2012-2023 AllelcoElec.com. All rights reserved.

Contact us

Address: Flat/Rm C 13/F Harvard Commercial Building 105-111 Thomson Road, Wan Chai, Hong Kong **Phone:** +00852 9146 4856

Fax: +00852 3010 8510

Email: info@Allelco.com