


# MBR140SFT1



## **Specifications**

MBR140SFT1 Tech Specifications MBR140SFT1 - onsemi technical specifications, attributes, parameters

| Product Attribute                 | Attribute Value                      | Product Attribute                | Attribute Value  |
|-----------------------------------|--------------------------------------|----------------------------------|------------------|
| Manufacturer                      | onsemi                               | Package                          | Tape & Reel (TR) |
| Voltage - Forward (Vf) (Max) @ If | 550 mV @ 1 A                         | Operating Temperature - Junction | -55°C ~ 125°C    |
| Voltage - DC Reverse (Vr) (Max)   | 40 V                                 | Mounting Type                    | Surface Mount    |
| Technology                        | Schottky                             | Current - Reverse Leakage @ Vr   | 500 µA @ 40 V    |
| Supplier Device Package           | SOD-123FL                            | Current - Average Rectified (Io) | 1A               |
| Speed                             | Fast Recovery =< 500ns, > 200mA (Io) | Capacitance @ Vr, F              | -                |
| Series                            | -                                    | Base Product Number              | MBR140           |
| Package / Case                    | SOD-123F                             |                                  |                  |

The three parts on the right have similar specifications to onsemi MBR140SFT1

| Product Attribute                       |                                      |                                      |                                      |                                      |
|---|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| Part Number                             | MBR140SFT1                           | MBR140SFT3G                          | MBR130T1H                            | MBR130T3                             |
| Manufacturer                            | onsemi                               | onsemi                               | onsemi                               | onsemi                               |
| Capacitance @ Vr, F                     | -                                    | -                                    | -                                    | -                                    |
| Speed                                   | Fast Recovery =< 500ns, > 200mA (Io) |
| Current - Average Rectified (Io)        | 1A                                   | 1A                                   | 1A                                   | 1A                                   |
| Series                                  | -                                    | -                                    | -                                    | -                                    |
| Voltage - Forward (Vf) (Max) @ If       | 550 mV @ 1 A                         | 550 mV @ 1 A                         | 450 mV @ 700 mA                      | 470 mV @ 1 A                         |
| Package                                 | Tape & Reel (TR)                     | Tape & Reel (TR)                     | Bulk                                 | Tape & Reel (TR)                     |
| Base Product Number                     | MBR140                               | MBR140                               | MBR130                               | MBR130                               |
| Technology                              | Schottky                             | Schottky                             | Schottky                             | Schottky                             |
| Package / Case                          | SOD-123F                             | SOD-123F                             | SOD-123                              | SOD-123                              |
| Voltage - DC Reverse (Vr) (Max)         | 40 V                                 | 40 V                                 | 30 V                                 | 30 V                                 |
| <b>Operating Temperature - Junction</b> | -55°C ~ 125°C                        | -55°C ~ 125°C                        | -65°C ~ 125°C                        | -65°C ~ 125°C                        |
| Current - Reverse Leakage @ Vr          | 500 μA @ 40 V                        | 500 µA @ 40 V                        | 60 μA @ 30 V                         | 60 µA @ 30 V                         |
| Supplier Device Package                 | SOD-123FL                            | SOD-123FL                            | SOD-123                              | SOD-123                              |
| Mounting Type                           | Surface Mount                        | Surface Mount                        | Surface Mount                        | Surface Mount                        |

### **MBR140SFT1** Datasheet PDF

Download MBR140SFT1 pdf datasheets and onsemi documentation for MBR140SFT1 - onsemi.

#### Datasheets

1

ዾ



#### **Environmental Information**

onsemi RoHS.pdf

#### PCN Assembly/Origin

Mult Dev Assembly Chgs 3/Jul/2020.pdf

### **Customers Also Interested in**

**Recommended Products** 





**NO PICTURE** 









| MBR140LT1G               | MBR140T1G   | MBR15150CT  | MBR140SFT3G                              | MBR130T1H                              | MBR140LSF   |
|--------------------------|---|---|--|--|---|
| AMI Semiconductor/onsemi | MSV   | Taiwan Semiconductor<br>Corporation<br>DIODE ARRAY SCHOTTKY 150V<br>TO220 | onsemi<br>DIODE SCHOTTKY 40V 1A SOD123FL | onsemi<br>DIODE SCHOTTKY 30V 1A SOD123 | PHY   |
| NO PICTURE               |   |   |  |  | DECDES PERICON INC.                                   |
| MBR140S                  | MBR15100CT  | MBR130T3  | MBR140SFT1G                              | MBR130T3G                              | MBR15100CTF-E1  |
| YEASHIN                  | Taiwan Semiconductor<br>Corporation<br>DIODE ARRAY SCHOTTKY 100V<br>TO220 | onsemi<br>DIODE SCHOTTKY 30V 1A SOD123                                    | onsemi<br>DIODE SCHOTTKY 40V 1A SOD123FL | onsemi<br>DIODE SCHOTTKY 30V 1A SOD123 | Diodes Incorporated<br>DIODE ARRAY SCHOTT 100V TO220F |
| NO PICTURE               |   |   |  | NO PICTURE                             | NO PICTURE  |
| MBR15100                 | MBR150G   | MBR140ESFT1G  | MBR140SFT3                               | MBR140SF                               | MBR140  |
| BCD                      | onsemi<br>DIODE SCHOTTKY 50V 1A AXIAL                                     | onsemi<br>DIODE SCHOTTKY 40V 1A SOD123FL                                  | onsemi<br>DIODE SCHOTTKY 40V 1A SOD123FL | SHIKUES                                | KEFAN   |

### **Shipment**

#### **Delivery Time**

In-stock items can be shipped within 24 hours. Some parts will be arranged for delivery within 1-2 days from the date all items arrive at our warehouse. And Allelco ships order once a day at about 17:00, except Sunday. Once the goods are shipped, the estimated delivery time depends on the shipping methods and Delivery destination. The table below shows are the logistic time for some common countries.

#### **Delivery Cost**

- > Use your express account for shipment if you have one.
- > Use our account for the shipment. Refer to the table below for the approximate charges.

(Different time frame / countries / package size has different price.)

#### **Delivery Method**

- > Global Common Shipment by DHL / UPS / FedEx / TNT / EMS / SF we support.
- > Others more shipping ways, please get in touch with your customer manager.

| Common Countries Logistic Time Reference |               |                    |  |
|--|---------------|--------------------|--|
| Region                                   | Country       | Logistic Time(Day) |  |
| America                                  | United States | 5                  |  |
| America                                  | Brazil        | 7                  |  |

| DHL & FedEx Shipment Charges Reference |                      |  |  |
|--|----------------------|--|--|
| Shipment charges(KG)                   | Reference DHL(USD\$) |  |  |
| 0.00kg-1.00kg                          | USD\$60.00           |  |  |
| 1.00kg-2.00kg                          | USD\$70.00           |  |  |

USD\$80.00

|             | Germany        | 5 |
|-------------|----------------|---|
| Europe      | United Kingdom | 4 |
|             | Italy          | 5 |
| Queenia     | Australia      | 6 |
| Oceania     | New Zealand    | 7 |
| Asia        | India          | 6 |
| Азіа        | Japan          | 7 |
| Middle East | Israel         | 6 |

Note: The above table is for reference only. There may have some data bias for the uncontrollable factors. Contact us if you have any questions.

### Payment Support

The payment method can be chosen from the methods shown below: Wire Transfer (T/T, Bank Transfer), Western Union, Credit card, PayPal.



## Your Faithful Supply Chain Partner -

影

ිදි

Efficient Supply Management

Cost-Saving Fast Sourcing & Procurement

4

Delivery

2.00kg-3.00kg





Email info@allelco.com Certifications & Memberships



View More



#### Contact us

Address: Flat/Rm C 13/F Harvard Commercial Building 105-111 Thomson Road, Wan Chai, Hong Kong Phone: +00852 9146 4856 Fax: +00852 3010 8510 Email: info@Allelco.com

