DAC8413EPZ



Image may be representation. See specifications for product details.

DAC8413EPZ

Data sheet

Manufacturer Part Number DAC8413EPZ

Manufacturer **Analog Devices, Inc.**

Allelco Part Number 32D-DAC8413EPZ

ECAD Model Request Free CAD Models

IC DAC 12BIT V-OUT 28DIP Parts Description

28-DIP (0.600", 15.24mm) Package

DAC8412,13.pdf

ROHS3 Compliant RoHs Status

Get a Quote



DAC8413EPZ - Analog Devices Inc..New Original in Stock. Download Linear Technology DAC8413EPZ datasheet/specifications on AllelcoElec.com. Request a quote for DAC8413EPZ, please send us email: info@allelco.com

Specifications

DAC8413EPZ Tech Specifications

DAC8413EPZ - Analog Devices Inc. technical specifications, attributes, parameters

	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Product Attribute	Attribute Value	Product Attribute	Attribute Value
Manufacturer	Analog Devices, Inc.	Operating Temperature	-40°C ~ 85°C
Voltage - Supply, Digital	5V	Number of D/A Converters	4
Voltage - Supply, Analog	5V ~ 15V, -15V	Number of Bits	12
Supplier Device Package	28-PDIP	Mounting Type	Through Hole
Settling Time	10μs (Typ)	INL/DNL (LSB)	±0.25, -1
Series	-	Differential Output	No
Reference Type	External	Data Interface	Parallel
Package / Case	28-DIP (0.600", 15.24mm)	Base Product Number	DAC8413
Package	Tube	Architecture	R-2R
Output Type	Voltage - Buffered		

Parts with Similar Specifications

The three parts on the right have similar specifications to Analog Devices Inc. DAC8413EPZ

Preduct Attribute DACM 1997					
Manufacturer Anabo Devices Inc. Anabo Devices	Product Attribute	William .	E THE THE PARTY OF		E THE THE PARTY OF
Mounting Type Through Hole Surface Mount Through Hole Surface Mount Package / Case 28-DDP (8-807, 13-24mm) 28-DDP (0-8017, 15-24mm) 28-DCP (1-805) INL/DNL (LSB) ±0.25, -1 ±2 (Mock), -1 ±2 (Mock), -1 ±2 (Mock), -1 Architecture 48-2k R-2k R-2k R-2k Operating Temperature -40°C - 80°C -40°C - 80°C -40°C - 80°C Package Tute Tute Tute Tute Number of D/A Converters 4 4 4 4 Voltage - Supply, Analog 59 ~ 159, -159 59 ~ 159, -159 59 ~ 159, -159 59 ~ 159, -159 Voltage - Supply, Digital 59 59 59 59 59 59 Output Type Voltage - Buffered Voltage - Buffered </td <td>Part Number</td> <td>DAC8413EPZ</td> <td>DAC8412FPCZ</td> <td>DAC8413FPZ</td> <td>DAC8412FPC</td>	Part Number	DAC8413EPZ	DAC8412FPCZ	DAC8413FPZ	DAC8412FPC
Package / Case 28-DIP (0.60P, 15.24mm) 28-CC (-1.4ady) 28-DIP (0.60P, 15.24mm) 28-LCC (-1.4ady) INL/DNL (USB) #0.25, -1 #2 (Mad), -1 #2 (Mad)	Manufacturer	Analog Devices Inc.	Analog Devices Inc.	Analog Devices Inc.	Analog Devices Inc.
INL/DNIL (LSB) +0.25, -1 +2 (Max), -1 -4 (Max) +2 (Max), -1 -4 (Max) +2 (Max), -1 -4 (Max) -1 -4 (Max) -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1	Mounting Type	Through Hole	Surface Mount	Through Hole	Surface Mount
Architecture R-2R	Package / Case	28-DIP (0.600", 15.24mm)	28-LCC (J-Lead)	28-DIP (0.600', 15.24mm)	28-LCC (J-Lead)
Operating Temperature -40°C ~ 85°C -40°C ~ 85°C -40°C ~ 85°C Package Tube Tube Tube Tube Number of D/A Converters 4 4 4 4 Voltage - Supply, Analog 5V ~ 15V, -15V 5V ~ 15V, -15V 5V ~ 15V, -15V Voltage - Supply, Digital 5V 5V 5V 5V Output Type Voltage - Buffered Settling Time 10µs (Typ) 10µs (Typ) 10µs (Typ) 10µs (Typ) 10µs (Typ) 10µs (Typ) Differential Output No No No No No No Data Interface Perallel Farallel Parallel	INL/DNL (LSB)	±0.25, -1	±2 (Max), -1	±2 (Max), -1	±2 (Max), -1
Package Tube Tube Tube Tube Number of D/A Converters 4 4 4 4 Voltage - Supply, Analog 5V ~ 15V, -15V 5V ~ 15V, -15V 5V ~ 15V, -15V 5V Voltage - Supply, Digital 5V 5V 5V 5V 5V Output Type Voltage - Buffered No	Architecture	R-2R	R-2R	R-2R	R-2R
Number of D/A Converters 4 4 4 4 Voltage - Supply, Analog 5V ~ 15V, -15V Voltage - Supply, Digital 5V 5V 5V 5V 5V Output Type Voltage - Buffered Settling Time 10µs (Typ) 10µs (Typ) 10µs (Typ) 10µs (Typ) Differential Output No No No No Data Interface Parallel Parallel Parallel Parallel Parallel Series - - - - - Supplier Device Package 28-PDIP 28-PLCC (11.51x11.51) 28-PDIP 28-PLCC (11.51x11.51) Base Product Number DAC8413 DAC8412 DAC8413 DAC8412 Reference Type External External External External	Operating Temperature	-40°C ∼ 85°C	-40°C ∼ 85°C	-40°C ∼ 85°C	-40°C ~ 85°C
Voltage - Supply, Analog 5V ~ 15V, -15V 5V ~ 15V, -15V 5V ~ 15V, -15V Voltage - Supply, Digital 5V 5V 5V 5V Output Type Voltage - Buffered Voltage - Buffered Voltage - Buffered Voltage - Buffered Settling Time 10µs (Typ) 10µs (Typ) 10µs (Typ) 10µs (Typ) Differential Output No No No No Data Interface Parallel Parallel Parallel Parallel Series - - - Supplier Device Package 28-PDIP 28-PLCC (11.51x11.51) 28-PDIP 28-PLCC (11.51x11.51) Base Product Number DAC8413 DAC8412 DAC8413 DAC8412 Reference Type External External External External External	Package	Tube	Tube	Tube	Tube
Voltage - Supply, Digital SV SV SV Output Type Voltage - Buffered Voltage - Buffered Voltage - Buffered Voltage - Buffered Settling Time 10µs (Typ) 10µs (Typ) 10µs (Typ) 10µs (Typ) Differential Output No No No Data Interface Parallel Parallel Parallel Parallel Series - - - Supplier Device Package 28-PDIP 28-PLCC (11.51x11.51) 28-PDIP 28-PLCC (11.51x11.51) Base Product Number DAC8413 DAC8412 DAC8413 DAC8412 Reference Type External External External External	Number of D/A Converters	4	4	4	4
Output Type Voltage - Buffered Voltage - Buffered Voltage - Buffered Settling Time 10µs (Typ) 10µs (Typ) 10µs (Typ) Differential Output No No No Data Interface Parallel Parallel Parallel Parallel Series - - - Supplier Device Package 28-PDIP 28-PLCC (11.51x11.51) 28-PDIP 28-PLCC (11.51x11.51) Base Product Number DAC8413 DAC8412 DAC8413 DAC8412 Reference Type External External External External External	Voltage - Supply, Analog	5V ~ 15V, -15V	5V ~ 15V, -15V	5V ~ 15V, -15V	5V ~ 15V, -15V
Settling Time 10µs (Typ) 10µs (Ty	Voltage - Supply, Digital	5V	5V	5V	5V
Differential Output No	Output Type	Voltage - Buffered	Voltage - Buffered	Voltage - Buffered	Voltage - Buffered
Data Interface Parallel Parallel Parallel Parallel Series - - - - Supplier Device Package 28-PDIP 28-PLCC (11.51x11.51) 28-PDIP 28-PLCC (11.51x11.51) Base Product Number DAC8413 DAC8412 DAC8413 DAC8412 Reference Type External External External External	Settling Time	10μs (Typ)	10μs (Typ)	10μs (Typ)	10μs (Typ)
Series	Differential Output	No	No	No	No
Supplier Device Package 28-PDIP 28-PLCC (11.51x11.51) 28-PDIP 28-PLCC (11.51x11.51) Base Product Number DAC8413 DAC8412 Reference Type External External External External	Data Interface	Parallel	Parallel	Parallel	Parallel
Base Product Number DAC8413 DAC8412 DAC8413 DAC8412 External External External	Series	-	-	-	-
Reference Type External External External External External	Supplier Device Package	28-PDIP	28-PLCC (11.51x11.51)	28-PDIP	28-PLCC (11.51x11.51)
	Base Product Number	DAC8413	DAC8412	DAC8413	DAC8412
Number of Bits 12 12 12	Reference Type	External	External	External	External
	Number of Bits	12	12	12	12

DAC8413EPZ Datasheet PDF

Download DAC8413EPZ pdf datasheets and Analog Devices Inc. documentation for DAC8413EPZ - Analog Devices Inc..

Datasheets



DAC8412,13.pdf

PCN Assembly/Origin



Mult Dev Assembly Trsf 7/Mar/2019.pdf

PCN Other



DAC8412/3 Redesign and Fab Process 01/Oct/2009.pdf

Customers Also Interested in

Recommended Products



DAC8412FPCZ Analog Devices Inc.

IC DAC 12BIT V-OUT 28PLCC



DAC8413FPZ Analog Devices Inc.

IC DAC 12BIT V-OUT 28DIP



DAC8412FPC

Analog Devices Inc. IC DAC 12BIT V-OUT 28PLCC



DAC8413FPCZ

Analog Devices Inc. IC DAC 12BIT V-OUT 28PLCC



DAC8413FP

Analog Devices Inc. IC DAC 12BIT V-OUT 28DIP



DAC8412FP

Analog Devices Inc. IC DAC 12BIT V-OUT 28DIP



DAC8420EPZ

Analog Devices Inc. IC DAC 12BIT V-OUT 16DIP



DAC8420ES

Analog Devices Inc. IC DAC 12BIT V-OUT 16SOIC



DAC8412F

ADI (Analog Devices, Inc.)



DAC8413FPC

Analog Devices Inc. IC DAC 12BIT V-OUT 28PLCC



DAC8420EP

Analog Devices Inc. IC DAC 12BIT V-OUT 16DIP



DAC8412EP

Analog Devices Inc. IC DAC 12BIT V-OUT 28DIP



DAC8413AT/883

ADI (Analog Devices, Inc.)



DAC8412FPCZ-REEL

Analog Devices Inc. IC DAC 12BIT V-OUT 28PLCC



DAC8413BT/883C

Analog Devices Inc. IC DAC 12BIT QUAD V-OUT 28CDIP



DAC8413F

ADI (Analog Devices, Inc.)



DAC8412FPC+

ADI (Analog Devices, Inc.)

► ANALOG DEVICES



DAC8412FPZ

Analog Devices Inc. IC DAC 12BIT V-OUT 28DIP

Shipment

Delivery Time

In-stock items can be shipped within 24 hours. Some parts will be arranged for delivery within 1-2 days from the date all items arrive at our warehouse. And Allelco ships order once a day at about 17:00, except Sunday. Once the goods are shipped, the estimated delivery time depends on the shipping methods and Delivery destination. The table below shows are the logistic time for some common countries.

Delivery Cost

- > Use your express account for shipment if you have one.
- > Use our account for the shipment. Refer to the table below for the approximate charges.

(Different time frame / countries / package size has different price.)

Delivery Method

- > Global Common Shipment by DHL / UPS / FedEx / TNT / EMS / SF we support.
- > Others more shipping ways, please get in touch with your customer manager.

Common Countries Logistic Time Reference				
Region	Country	Logistic Time(Day)		
America	United States	5		
America	Brazil	7		
	Germany	5		
Europe	United Kingdom	4		
	Italy	5		
Oceania	Australia	6		
Oceania	New Zealand	7		
Asia	India	6		
ASIA	Japan	7		
Middle East	Israel	6		

DHL & FedEx Shipment Charges Reference				
Shipment charges(KG)	Reference DHL(USD\$)			
0.00kg-1.00kg	USD\$60.00			
1.00kg-2.00kg	USD\$70.00			
2.00kg-3.00kg	USD\$80.00			

Note: The above table is for reference only. There may have some data bias for the uncontrollable factors. Contact us if you have any questions.

Payment Support

The payment method can be chosen from the methods shown below: Wire Transfer (T/T, Bank Transfer), Western Union, Credit card, PayPal.













Your Faithful Supply Chain Partner -



Management





Fast Sourcing &

Delivery



Procurement



Phone +00852 9146 4856



Email info@allelco.com

Certifications & Memberships













View More