



Image may be representation.
See specifications for product details.



293D106X9025D2TE3

Manufacturer Part Number	293D106X9025D2TE3
Manufacturer	Vishay / Sprague
Allelco Part Number	32D-293D106X9025D2TE3
ECAD Model	PCB Symbol, Footprint & 3D Model
Parts Description	CAP TANT 10UF 10% 25V 2917
Package	2917 (7343 Metric)
Data sheet	293D Series Datasheet.pdf 293D Series Datasheet.pdf
RoHs Status	ROHS3 Compliant

[Get a Quote](#)

293D106X9025D2TE3 - Vishay Sprague. New Original in Stock. Download Linear Technology 293D106X9025D2TE3 datasheet/specifications on AllelcoElec.com. Request a quote for 293D106X9025D2TE3, please send us email: info@allelco.com

Specifications

293D106X9025D2TE3 Tech Specifications
293D106X9025D2TE3 - Vishay Sprague technical specifications, attributes, parameters

Product Attribute	Attribute Value	Product Attribute	Attribute Value
Manufacturer	Vishay / Sprague	Mounting Type	Surface Mount
Voltage - Rated	25 V	Manufacturer Size Code	D
Type	Molded	Lifetime @ Temp.	-
Tolerance	±10%	Lead Spacing	-
Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)	Height - Seated (Max)	0.122" (3.10mm)
Series	TANTAMOUNT®, 293D	Features	General Purpose
Package / Case	2917 (7343 Metric)	Failure Rate	-
Package	Tape & Reel (TR)	ESR (Equivalent Series Resistance)	10Ohm
Operating Temperature	-55°C ~ 125°C	Capacitance	10 µF

Parts with Similar Specifications

The three parts on the right have similar specifications to Vishay Sprague 293D106X9025D2TE3

Product Attribute				
Part Number	293D106X9025D2TE3	293D107X0010C2TE3	293D106X9035C2TE3	293D106X9035D2TE3
Manufacturer	Vishay Sprague	Vishay Sprague	Vishay Sprague	Vishay Sprague
Voltage - Rated	25 V	10 V	35 V	35 V
Manufacturer Size Code	D	C	C	D
Package / Case	2917 (7343 Metric)	2312 (6032 Metric)	2312 (6032 Metric)	2917 (7343 Metric)
Package	Tape & Reel (TR)	Tape & Reel (TR)	Tape & Reel (TR)	Tape & Reel (TR)
Operating Temperature	-55°C ~ 125°C	-55°C ~ 125°C	-55°C ~ 125°C	-55°C ~ 125°C
Features	General Purpose	General Purpose	General Purpose	General Purpose
Mounting Type	Surface Mount	Surface Mount	Surface Mount	Surface Mount
Lifetime @ Temp.	-	-	-	-
Capacitance	10 µF	100 µF	10 µF	10 µF
Type	Molded	Molded	Molded	Molded
Tolerance	±10%	±20%	±10%	±10%
Height - Seated (Max)	0.122" (3.10mm)	0.110" (2.79mm)	0.110" (2.79mm)	0.122" (3.10mm)
Lead Spacing	-	-	-	-
Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)	0.236" L x 0.126" W (6.00mm x 3.20mm)	0.236" L x 0.126" W (6.00mm x 3.20mm)	0.287" L x 0.169" W (7.30mm x 4.30mm)
Failure Rate	-	-	-	-
Series	TANTAMOUNT®, 293D	TANTAMOUNT®, 293D	TANTAMOUNT®, 293D	TANTAMOUNT®, 293D
ESR (Equivalent Series Resistance)	10hm	900mOhm	1.6Ohm	800mOhm

293D106X9025D2TE3 Datasheet PDF

Download 293D106X9025D2TE3 pdf datasheets and Vishay Sprague documentation for 293D106X9025D2TE3 - Vishay Sprague.

Datasheets

[293D Series Datasheet.pdf](#)

HTML Datasheet

[293D Series Datasheet.pdf](#)

PCN Design/Specification

[Adding of Halogen Free Id 23/Dec/2014.pdf](#)

Customers Also Interested in

Recommended Products

					
293D106X9025B2T Electro-Films (EFI) / Vishay	293D107X0010B2TE3 Electro-Films (EFI) / Vishay	293D106X9035D2T Electro-Films (EFI) / Vishay	293D106X9035D2Y400 Electro-Films (EFI) / Vishay	293D107X0010C2TE3 Vishay Sprague CAP TANT 100UF 20% 10V 2312	293D106X9016D2TE3 Electro-Films (EFI) / Vishay
					
293D106X9035C2TE3 Vishay Sprague CAP TANT 10UF 10% 35V 2312	293D106X9035D2TE3 Vishay Sprague CAP TANT 10UF 10% 35V 2917	293D106X9025C2S610 Electro-Films (EFI) / Vishay	293D106X9025C2W175 Electro-Films (EFI) / Vishay	293D106X9025C2TE3 Vishay Sprague CAP TANT 10UF 10% 25V 2312	293D106X9020B2TE3 Vishay Sprague CAP TANT 10UF 10% 20V 1411
					
293D106X9025B2TE3 Vishay Sprague TANTALUM CAP 10000000 PF 10%	293D106X9020D2T Electro-Films (EFI) / Vishay	293D106X96R3B2TE3 Vishay Sprague CAP TANT 10UF 10% 6.3V 1411	293D107X0010D2TE3 Vishay Sprague CAP TANT 100UF 20% 10V 2917	293D106X96R3A2TE3 Vishay Sprague CAP TANT 10UF 10% 6.3V 1206	293D106X9025C2T VIS

Shipment

Delivery Time

In-stock items can be shipped within 24 hours. Some parts will be arranged for delivery within 1-2 days from the date all items arrive at our warehouse. And Allelco ships order once a day at about 17:00, except Sunday. Once the goods are shipped, the estimated delivery time depends on the shipping methods and Delivery destination. The table below shows are the logistic time for some common countries.

Delivery Cost

- > Use your express account for shipment if you have one.
- > Use our account for the shipment. Refer to the table below for the approximate charges.
(Different time frame / countries / package size has different price.)

Delivery Method

- > Global Common Shipment by DHL / UPS / FedEx / TNT / EMS / SF we support.
- > Others more shipping ways, please get in touch with your customer manager.

Common Countries Logistic Time Reference		
Region	Country	Logistic Time(Day)
America	United States	5
	Brazil	7
Europe	Germany	5
	United Kingdom	4
	Italy	5
Oceania	Australia	6
	New Zealand	7
Asia	India	6
	Japan	7
Middle East	Israel	6

DHL & FedEx Shipment Charges Reference	
Shipment charges(KG)	Reference DHL(USD\$)
0.00kg-1.00kg	USD\$60.00
1.00kg-2.00kg	USD\$70.00
2.00kg-3.00kg	USD\$80.00

Note: The above table is for reference only. There may have some data bias for the uncontrollable factors.
Contact us if you have any questions.

Payment Support

The payment method can be chosen from the methods shown below:
Wire Transfer (T/T, Bank Transfer), Western Union, Credit card, PayPal.



Your Faithful Supply Chain Partner -

-  Efficient Supply Management
-  Cost-Saving Procurement
-  Fast Sourcing & Delivery

Contact us if you have any questions.

-  Phone
+00852 9146 4856
-  Email
info@allelco.com

Certifications & Memberships



[View More](#)