

NRVUS240VT3G

Manufacturer Part Number NRVUS240VT3G

Manufacturer onsemi

Allelco Part Number 32D-NRVUS240VT3G

ECAD Model Request Free CAD Models

DIODE GEN PURP 400V 2A SMB Parts Description

DO-214AA, SMB Package

Data sheet

ROHS3 Compliant RoHs Status

Get a Quote

Image may be representation.

See specifications for product details.



Request a quote for NRVUS240VT3G, please send us email: info@allelco.com

NRVUS240VT3G - onsemi.New Original in Stock. Download Linear Technology NRVUS240VT3G datasheet/specifications on AllelcoElec.com.

MURS230, 240 T3.pdf

Specifications

NRVUS240VT3G Tech Specifications

NRVUS240VT3G - onsemi technical specifications, attributes, parameters

Product Attribute	Attribute Value	Product Attribute	Attribute Value
Manufacturer	onsemi	Package / Case	DO-214AA, SMB
Voltage - Forward (Vf) (Max) @ If	1.3 V @ 2 A	Package	Tape & Reel (TR)
Voltage - DC Reverse (Vr) (Max)	400 V	Operating Temperature - Junction	-65°C ~ 175°C
Technology	Standard	Mounting Type	Surface Mount
Supplier Device Package	SMB	Current - Reverse Leakage @ Vr	5 μA @ 400 V
Speed	Fast Recovery =< 500ns, > 200mA (Io)	Current - Average Rectified (Io)	2A
Series	Automotive, AEC-Q101	Capacitance @ Vr, F	-
Reverse Recovery Time (trr)	65 ns	Base Product Number	NRVUS240

Parts with Similar Specifications

The three parts on the right have similar specifications to onsemi NRVUS240VT3G

The three parts on the right have similar specifications to onsemi NRVUS240VT3G				
Product Attribute				
Part Number	NRVUS240VT3G	NRVUS120VT3G	NRVUHS160VT3G	NRVUS360VDBT3G
Manufacturer	onsemi	onsemi	onsemi	onsemi
Capacitance @ Vr, F	-	-	-	-
Operating Temperature - Junction	-65°C ~ 175°C	-65°C ~ 175°C	-65°C ~ 175°C	-65°C ~ 175°C
Voltage - Forward (Vf) (Max) @ If	1.3 V @ 2 A	875 mV @ 1 A	2.4 V @ 1 A	1.25 V @ 3 A
Current - Average Rectified (Io)	2A	2A	1A	3A
Base Product Number	NRVUS240	NRVUS120	NRVUHS160	NRVUS360
Reverse Recovery Time (trr)	65 ns	35 ns	35 ns	75 ns
Package	Tape & Reel (TR)			
Mounting Type	Surface Mount	Surface Mount	Surface Mount	Surface Mount
Technology	Standard	Standard	Standard	Standard
Supplier Device Package	SMB	SMB	SMB	SMB
Voltage - DC Reverse (Vr) (Max)	400 V	200 V	600 V	600 V
Package / Case	DO-214AA, SMB	DO-214AA, SMB	DO-214AA, SMB	DO-214AA, SMB
Speed	Fast Recovery =< 500ns, > 200mA (Io)			
Current - Reverse Leakage @ Vr	5 μA @ 400 V	2 μA @ 200 V	20 μA @ 600 V	3 μA @ 600 V
Series	Automotive, AEC-Q101	Automotive, AEC-Q101	Automotive, AEC-Q101	Automotive, AEC-Q101

NRVUS240VT3G Datasheet PDF

Download NRVUS240VT3G pdf datasheets and onsemi documentation for NRVUS240VT3G - onsemi.

Datasheets

MURS230, 240 T3.pdf

Environmental Information

onsemi REACH.pdf onsemi RoHS.pdf


PCN Assembly/Origin

Transfer of Assembly and Test 20/Dec/2022.pdf


Customers Also Interested in

Recommended Products













NRVUD620CTT4G

onsemi DIODE ARRAY GP 200V 3A DPAK



onsemi DIODE GEN PURP 200V 2A SMB



onsemi DIODE GEN PURP 600V 1A SMB

NRVUS360VDBT3G

onsemi DIODE GEN PURP 600V 3A SMB

NRVUS1MFA

onsemi DIODE GEN PURP 1KV 1A SOD123FL NRVUS160VT3G onsemi

DIODE GEN PURP 600V 2A SMB













NRVUS1KFA

onsemi DIODE GEN PURP 800V 1A SOD123FL



onsemi DIODE GEN PURP 600V 1A



onsemi DIODE GEN PURP 520V 5A DPAK

NRVUS1DFA

onsemi

DIODE GEN PURP 200V 1A

SOD123FL



NRVUS2GA

onsemi



NRVUS110VT3G onsemi


DIODE GEN PURP 100V 2A SMB



NRVUS220VT3G

onsemi

DIODE GEN PURP 200V 2A SMB






DIODE GEN PURP 400V 1.5A DO214AC





NRVUS360VBT3G

onsemi DIODE GEN PURP 600V 3A SMB



NRVUS1FFA


onsemi

DIODE GEN PURP 300V 1A

SOD123FL

NRVUS230T3G

onsemi DIODE GEN PURP 300V 2A SMB



NRVUS230VT3G

onsemi DIODE GEN PURP 300V 2A SMB



NRVUS240T3G

onsemi DIODE GEN PURP 400V 2A SMB

Shipment

In-stock items can be shipped within 24 hours. Some parts will be arranged for delivery within 1-2 days from the date all items arrive at our warehouse. And Allelco ships order once a day at about 17:00, except Sunday. Once the goods are shipped, the estimated delivery time depends on the shipping methods and Delivery destination. The table below shows are the logistic time for some common countries.

Delivery Cost

- > Use your express account for shipment if you have one.
- > Use our account for the shipment. Refer to the table below for the approximate charges.

(Different time frame / countries / package size has different price.)

Delivery Method

- > Global Common Shipment by DHL / UPS / FedEx / TNT / EMS / SF we support.
- > Others more shipping ways, please get in touch with your customer manager.

Common Countries Logistic Time Reference				
Region	Country	Logistic Time(Day)		
America	United States	5		
America	Brazil	7		
	Germany	5		
Europe	United Kingdom	4		
	Italy	5		
Oceania	Australia	6		
Oceania	New Zealand	7		
Asia	India	6		
Asia	Japan	7		
Middle East	Israel	6		

DHL & FedEx Shipment Charges Reference			
Shipment charges(KG)	Reference DHL(USD\$)		
0.00kg-1.00kg	USD\$60.00		
1.00kg-2.00kg	USD\$70.00		
2.00kg-3.00kg	USD\$80.00		

Note: The above table is for reference only. There may have some data bias for the uncontrollable factors. Contact us if you have any questions.

Payment Support

The payment method can be chosen from the methods shown below: Wire Transfer (T/T, Bank Transfer), Western Union, Credit card, PayPal.








PayPal

















Phone +00852 9146 4856



Certifications & Memberships













View More



Copyright © 2012-2023 AllelcoElec.com. All rights reserved.

Contact us

Address: Flat/Rm C 13/F Harvard Commercial Building 105-111 Thomson Road, Wan Chai, Hong Kong **Phone:** +00852 9146 4856

Email: info@Allelco.com

Fax: +00852 3010 8510