

Image may be representation.
See specifications for product details.



EMIF02-MIC03F2

Manufacturer Part Number	EMIF02-MIC03F2
Manufacturer	STMicroelectronics
Allelco Part Number	32D-EMIF02-MIC03F2
ECAD Model	PCB Symbol, Footprint & 3D Model
Parts Description	IC EMI FILTER ESD PROT SMD
Package	5-WFBGA, FCBGA
Data sheet	EMIF02-MIC03F2.pdf
RoHs Status	ROHS3 Compliant

Get a Quote

EMIF02-MIC03F2 - STMicroelectronics.New Original in Stock. Download Linear Technology EMIF02-MIC03F2 datasheet/specifications on AllelcoElec.com.
Request a quote for EMIF02-MIC03F2, please send us email: info@allelco.com

Specifications

EMIF02-MIC03F2 Tech Specifications
EMIF02-MIC03F2 - STMicroelectronics technical specifications, attributes, parameters

Product Attribute	Attribute Value	Product Attribute	Attribute Value
Manufacturer	STMicroelectronics	Operating Temperature	-40°C ~ 85°C
Voltage - Rated	-	Number of Channels	2
Values	R = 68Ohms, C = 100pF	Mounting Type	Surface Mount
Type	Low Pass	Height	0.028" (0.70mm)
Technology	RC (Pi)	Filter Order	2nd
Size / Dimension	0.058" L x 0.042" W (1.47mm x 1.07mm)	ESD Protection	Yes
Series	EMIF	Center / Cutoff Frequency	-
Resistance - Channel (Ohms)	68	Base Product Number	EMIF02
Package / Case	5-WFBGA, FCBGA	Attenuation Value	-
Package	Tape & Reel (TR)	Applications	Data Lines for Mobile Devices

Parts with Similar Specifications

The three parts on the right have similar specifications to STMicroelectronics EMIF02-MIC03F2

Product Attribute				
Part Number	EMIF02-MIC03F2	EMIF02-MIC06F3	EMIF01-SMIC01F2	EMIF02-SPK03F2
Manufacturer	STMicroelectronics	STMicroelectronics	STMicroelectronics	STMicroelectronics
Applications	Data Lines for Mobile Devices	Data Lines for Mobile Devices	Audio	Audio
Size / Dimension	0.058" L x 0.042" W (1.47mm x 1.07mm)	0.047" L x 0.047" W (1.20mm x 1.20mm)	-	0.050" L x 0.035" W (1.26mm x 0.89mm)
Technology	RC (Pi)	RC (Pi)	-	LC (Pi)
Attenuation Value	-	-	-	-40dB @ 900MHz
Mounting Type	Surface Mount	Surface Mount	Surface Mount	Surface Mount
Type	Low Pass	Low Pass	Low Pass	Low Pass
Number of Channels	2	2	1	2
Series	EMIF	EMIF	IPAD™	EMIF
Operating Temperature	-40°C ~ 85°C	-40°C ~ 85°C	-40°C ~ 85°C	-30°C ~ 85°C
Values	R = 68Ohms, C = 100pF	R = 5.225kOhms (Total), C = 2.05nF (Total)	-	C = 250pF
Height	0.028" (0.70mm)	0.026" (0.66mm)	-	0.028" (0.70mm)
Voltage - Rated	-	-	-	-
Package	Tape & Reel (TR)	Tape & Reel (TR)	Tape & Reel (TR)	Tape & Reel (TR)
Filter Order	2nd	2nd	-	3rd
Resistance - Channel (Ohms)	68	-	-	0.07
ESD Protection	Yes	Yes	Yes	Yes
Center / Cutoff Frequency	-	-	-	-
Base Product Number	EMIF02	EMIF02	EMIF01	EMIF02
Package / Case	5-WFBGA, FCBGA	8-UFBGA, FCBGA	8-UFBGA, FCBGA	5-WFBGA, FCBGA

EMIF02-MIC03F2 Datasheet PDF

Download EMIF02-MIC03F2 pdf datasheets and STMicroelectronics documentation for EMIF02-MIC03F2 - STMicroelectronics.

PCN Packaging






Label 17/Jan/2019.pdf

HTML Datasheet

EMIF02-MIC03F2.pdf

Customers Also Interested in

Recommended Products

 life.augmented	 life.augmented		 life.augmented	 life.augmented	
EMIF02-MIC06F3 STMicroelectronics IC EMI FILTER ESD PROT SMD	EMIF01-SMIC01F2 STMicroelectronics FILTER ESD SMD	EMIF02-SPK03F2 STMicroelectronics FILTER LC(PI) 250PF ESD SMD	EMIF02-MIC02F2A7 STMicroelectronics	EMIF02-SPK01F STMicroelectronics	EMIF02-SPK02F2 STMicroelectronics IC EMI FILTER ESD PROT SMD
 life.augmented	 life.augmented		 life.augmented		
EMIF02-MIC02F1 STMicroelectronics	EMIF02-600FU7 STMicroelectronics	EMIF02-AV01F3 STMicroelectronics FILTER RC(PI) 15 OHM/3200PF SMD	EMIF02-MIC6RF3B7 STMicroelectronics	EMIF02-MIC03M6 STMicroelectronics IC EMI FILTER ESD PROT SMD	EMIF02-MIC02F2 STMicroelectronics FILTER RC(PI) 470 OHM/16PF SMD
 life.augmented			 life.augmented	 life.augmented	
EMIF02-MIC05F2 STMicroelectronics	EMIF02-1003M6 STMicroelectronics IC EMI FILTER 2LINE 6-MICRO QFN	EMIF02-02OABRY STMicroelectronics FILTER 2LINE 6QFN	EMIF01-5250SC5 STMicroelectronics	EMIF02-SPK01C2 STMicroelectronics FILTER RC(PI) 10 OHM/200PF SMD	EMIF02-MIC02F3 STMicroelectronics FILTER RC(PI) 470 OHM/16PF SMD

Shipment

Delivery Time

In-stock items can be shipped within 24 hours. Some parts will be arranged for delivery within 1-2 days from the date all items arrive at our warehouse. And Allelco ships order once a day at about 17:00, except Sunday. Once the goods are shipped, the estimated delivery time depends on the shipping methods and Delivery destination. The table below shows are the logistic time for some common countries.

Delivery Cost

> Use your express account for shipment if you have one.

> Use our account for the shipment. Refer to the table below for the approximate charges.

(Different time frame / countries / package size has different price.)

Delivery Method

> Global Common Shipment by DHL / UPS / FedEx / TNT / EMS / SF we support.

> Others more shipping ways, please get in touch with your customer manager.

Common Countries Logistic Time Reference		
Region	Country	Logistic Time(Day)
America	United States	5
	Brazil	7
Europe	Germany	5
	United Kingdom	4
	Italy	5
Oceania	Australia	6
	New Zealand	7
Asia	India	6
	Japan	7
Middle East	Israel	6

DHL & FedEx Shipment Charges Reference	
Shipment charges(KG)	Reference DHL(USD\$)
0.00kg-1.00kg	USD\$60.00
1.00kg-2.00kg	USD\$70.00
2.00kg-3.00kg	USD\$80.00




Note: The above table is for reference only. There may have some data bias for the uncontrollable factors.
Contact us if you have any questions.

Payment Support



The payment method can be chosen from the methods shown below:
Wire Transfer (T/T, Bank Transfer), Western Union, Credit card, PayPal.



Your Faithful Supply Chain Partner -

 Efficient Supply Management
 Cost-Saving Procurement
 Fast Sourcing & Delivery

Contact us if you have any questions.

 Phone
+00852 9146 4856
 Email
info@allelco.com

Certifications & Memberships



[View More](#)