

STP4N52K3

Package

Manufacturer Part Number STP4N52K3

Manufacturer STMicroelectronics

Allelco Part Number 32D-STP4N52K3

ECAD Model

PCB Symbol, Footprint & 3D Mode

Parts Description MOSFET N-CH 525V 2.5A TO220

TO-220-3

Data sheet STx4N52K3.pdf

RoHs Status ROHS3 Compliant

Get a Quote



Image may be representation.

See specifications for product details.

STP4N52K3 - STMicroelectronics.New Original in Stock. Download Linear Technology STP4N52K3 datasheet/specifications on AllelcoElec.com. Request a quote for STP4N52K3, please send us email: info@allelco.com

Specifications

STP4N52K3 Tech Specifications

STP4N52K3 - STMicroelectronics technical specifications, attributes, parameters

The market of the technical specifications, defibrates, parameters				
Product Attribute	Attribute Value	Product Attribute	Attribute Value	
Manufacturer	STMicroelectronics	Operating Temperature	150°C (TJ)	
Vgs(th) (Max) @ Id	4.5V @ 50µA	Mounting Type	Through Hole	
Vgs (Max)	±30V	Input Capacitance (Ciss) (Max) @ Vds	334 pF @ 100 V	
Technology	MOSFET (Metal Oxide)	Gate Charge (Qg) (Max) @ Vgs	11 nC @ 10 V	
Supplier Device Package	TO-220	FET Type	N-Channel	
Series	SuperMESH3™	FET Feature	-	
Rds On (Max) @ Id, Vgs	2.60hm @ 1.25A, 10V	Drive Voltage (Max Rds On, Min Rds On)	10V	
Power Dissipation (Max)	45W (Tc)	Drain to Source Voltage (Vdss)	525 V	
Package / Case	TO-220-3	Current - Continuous Drain (Id) @ 25°C	2.5A (Tc)	
Package	Tube	Base Product Number	STP4N52	

Parts with Similar Specifications

The three parts on the right have similar specifications to STMicroelectronics STP4N52K3

The three parts on the right have similar spec	eclifications to STMicroelectronics STF-IN32NS			
Product Attribute				
Part Number	STP4N52K3	STP4N80K5	STP4N62K3	STP4LN80K5
Manufacturer	STMicroelectronics	STMicroelectronics	STMicroelectronics	STMicroelectronics
Supplier Device Package	TO-220	TO-220	TO-220	TO-220
Vgs(th) (Max) @ Id	4.5V @ 50μA	5V @ 100μA	4.5V @ 50μA	5V @ 100μA
Package / Case	TO-220-3	TO-220-3	TO-220-3	TO-220-3
Package	Tube	Tube	Tube	Tube
FET Type	N-Channel	N-Channel	N-Channel	N-Channel
Mounting Type	Through Hole	Through Hole	Through Hole	Through Hole
Operating Temperature	150°C (TJ)	-55°C ~ 150°C (TJ)	150°C (TJ)	-55°C ∼ 150°C (TJ)
Input Capacitance (Ciss) (Max) @ Vds	334 pF @ 100 V	175 pF @ 100 V	450 pF @ 50 V	122 pF @ 100 V
Drive Voltage (Max Rds On, Min Rds On)	10V	10V	10V	10V
FET Feature	-	-	-	-
Series	SuperMESH3™	SuperMESH5 [™]	SuperMESH3™	MDmesh™ K5
Vgs (Max)	±30V	±30V	±30V	±30V
Base Product Number	STP4N52	STP4N80	STP4N	STP4LN80
Power Dissipation (Max)	45W (Tc)	60W (Tc)	70W (Tc)	60W (Tc)
Current - Continuous Drain (Id) @ 25°C	2.5A (Tc)	3A (Tc)	3.8A (Tc)	3A (Tc)
Technology	MOSFET (Metal Oxide)	MOSFET (Metal Oxide)	MOSFET (Metal Oxide)	MOSFET (Metal Oxide)
Drain to Source Voltage (Vdss)	525 V	800 V	620 V	800 V
Rds On (Max) @ Id, Vgs	2.60hm @ 1.25A, 10V	2.50hm @ 1.5A, 10V	1.950hm @ 1.9A, 10V	2.60hm @ 1A, 10V
Gate Charge (Qg) (Max) @ Vgs	11 nC @ 10 V	10.5 nC @ 10 V	14 nC @ 10 V	3.7 nC @ 10 V

▼ STP4N52K3 Datasheet PDF

Download STP4N52K3 pdf datasheets and STMicroelectronics documentation for STP4N52K3 - STMicroelectronics.

Datasheets



PCN Design/Specification



Mult Dev Adv Material Notice 8/Apr/2019.pdf

PCN Assembly/Origin



TO-220 Capacity Expansion 18/Jun/2013.pdf

Customers Also Interested in

Recommended Products















STP4953MRG

VBSEMI

STP4N100FI

STMicroelectronics

STP4N100

STMicroelectronics

STP4N80K5 STMicroelectronics MOSFET N-CH 800V 3A TO220 **STP4NA60FP MOS**

STMicroelectronics

life.augmented

STP4N80K5 MOS

STMicroelectronics













STP4NA60

STMicroelectronics



MOSFET N-CH 620V 3.8A TO220

STP4953M-TRG

SEMTRON

STP4LN80K5

STMicroelectronics MOSFET N-CHANNEL 800V 3A TO220

STP4CMPQTR STMicroelectronics IC LED DRVR RGLTR PWM 30MA 20QFN

STP4N150

STMicroelectronics MOSFET N-CH 1500V 4A TO220AB







NO PICTURE





life.augmented

STMicroelectronics



STP4N25

STMicroelectronics

STP4NA60FI STMicroelectronics STP4A60S

SEMIWELL

STP4NA60FP

STMicroelectronics

STP4N20

STP4N90K5

STMicroelectronics MOSFET N-CH 900V 3A TO220

Shipment

Delivery Time

In-stock items can be shipped within 24 hours. Some parts will be arranged for delivery within 1-2 days from the date all items arrive at our warehouse. And Allelco ships order once a day at about 17:00, except Sunday. Once the goods are shipped, the estimated delivery time depends on the shipping methods and Delivery destination. The table below shows are the logistic time for some common countries.

Delivery Cost

- > Use your express account for shipment if you have one.
- > Use our account for the shipment. Refer to the table below for the approximate charges.

(Different time frame / countries / package size has different price.)

Delivery Method

- > Global Common Shipment by DHL / UPS / FedEx / TNT / EMS / SF we support.
- > Others more shipping ways, please get in touch with your customer manager.

Common Countries Logistic Time Reference				
Region	Country	Logistic Time(Day)		
America	United States	5		
	Brazil	7		
Europe	Germany	5		
	United Kingdom	4		
	Italy	5		
Oceania	Australia	6		
	New Zealand	7		
Acia	India	6		
Asia	Japan	7		
Middle East	Israel	6		

DHL & FedEx Shipment Charges Reference			
Shipment charges(KG)	Reference DHL(USD\$)		
0.00kg-1.00kg	USD\$60.00		
1.00kg-2.00kg	USD\$70.00		
2.00kg-3.00kg	USD\$80.00		

Note: The above table is for reference only. There may have some data bias for the uncontrollable factors. Contact us if you have any questions.

Payment Support

The payment method can be chosen from the methods shown below: Wire Transfer (T/T, Bank Transfer), Western Union, Credit card, PayPal.










Your Faithful Supply Chain Partner -













+00852 9146 4856

Email

info@allelco.com

Certifications & Memberships













View More